www.jinkosolar.com

Building **Your Trust** in Solar

Tiger Neo N-type 54HL4R-(V)

425-450 Watt

MONO-FACIAL MODULE

N-Type

Positive power tolerance of 0~+3%

IEC61215(2016), IEC61730(2016)

ISO9001:2015: Quality Management System

ISO14001:2015: Environment Management System

ISO45001:2018
Occupational health and safety management systems



Key Features

SMBB Technology

Better light trapping and current collection to improve module power output and reliability.

Hot 2.0 Technology

The N-type module with Hot 2.0 technology has better reliability and lower LID/LeTID.

PID Resistance

Excellent Anti-PID performance guarantee via optimized mass-production process and materials control.

Enhanced Mechanical Load

Certified to withstand: wind load (4000 Pascal) and snow load (6000 Pascal).

Durability Against Extreme Environmental Conditions

High salt mist and ammonia resistance.

LINEAR PERFORMANCE WARRANTY



15 Year Product Warranty

30 Year Linear Power Warranty

0.40% Annual Degradation Over 30 years

Engineering Drawings



Front Side Back



Length: ±2mm
Width: ±2mm
Height: ±1mm
Row Pitch: ±2mm

Packaging Configuration

(Two pallets = One stack)

36pcs/pallets, 72pcs/stack, 936pcs/ 40'HQ Container

Electrical Performance & Temperature Dependence

Current-Voltage & Power-Voltage Curves (435W)



Temperature Dependence of Isc,Voc,Pmax



Mechanical Characteristics

Cell Type	N type Mono-crystalline
No. of cells	108 (2×54)
Dimensions	1762×1134×30mm (69.36×44.65×1.18 inch)
Weight	22 kg (48.50 lbs)
Front Glass	3.2mm,Anti-Reflection Coating, High Transmission, Low Iron, Tempered Glass
Frame	Anodized Aluminium Alloy
Junction Box	IP68 Rated
Output Cables	TUV 1×4.0mm² (+): 400mm , (-): 200mm or Customized Length

SPECIFICATIONS

Module Type	JKM425N-54HL4R JKM425N-54HL4R-V		JKM430N-54HL4R JKM430N-54HL4R-V		JKM435N-54HL4R JKM435N-54HL4R-V		JKM440N-54HL4R JKM440N-54HL4R-V		JKM445N-54HL4R JKM445N-54HL4R-V		JKM450-54HL4R JKM450N-54HL4R-V	
	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT
Maximum Power (Pmax)	425Wp	320Wp	430Wp	323Wp	435Wp	327Wp	440Wp	331Wp	445Wp	335Wp	450Wp	338Wp
Maximum Power Voltage (Vmp)	32.18V	29.99V	32.38V	30.10V	32.59V	30.33V	32.81V	30.56V	33.02V	30.76V	33.21V	30.90V
Maximum Power Current (Imp)	13.21A	10.67A	13.28A	10.73A	13.35A	10.78A	13.41A	10.83A	13.48A	10.89A	13.55A	10.94A
Open-circuit Voltage (Voc)	38.75V	36.81V	38.95V	37.00V	39.16V	37.20V	39.38V	37.41V	39.59V	37.61V	39.78V	37.79V
Short-circuit Current (Isc)	13.66A	11.03A	13.73A	11.09A	13.80A	11.14A	13.86A	11.19A	13.93A	11.25A	14.00A	11.30A
Module Efficiency STC (%)	21.27%		21.52%		21.77%		22.02%		22.27%		22.52%	
Operating Temperature(℃)	-40℃~+85℃											
Maximum system voltage	1000/1500VDC (IEC)											
Maximum series fuse rating	25A											
Power tolerance	0~+3%											
Temperature coefficient of Pmax	-0.29%/℃											
Temperature coefficient of Voc	-0.25%/℃											
Temperature coefficient of Isc	0.045%/℃											
Nominal operating cell temperature (NOCT)	45±2℃											

*STC: Irradiance 1000W/m² Cell Temperature 25℃ AM=1.5

NOCT: Irradiance 800W/m² Ambient Temperature 20℃ AM=1.5 Wind Speed 1m/s

©2022 Jinko Solar Co., Ltd. All rights reserved.
Specifications included in this datasheet are subject to change without notice.